



NEW !

The **first battery operated wireless μfocus** X-ray generator for industrial NDT application



KEY SPECIFICATIONS

- ▶ Selectable kV: 50 to 120 kV
- ▶ Selectable mA: 0,1 - 2mA
- ▶ Constant potential
- ▶ **Focal spot: 0.2mm (ASTM E1165-12, BAM approved)**
- ▶ Beam angle: 45° x 45°
- ▶ Oil insulated
- ▶ Powered from the main or from batteries
- ▶ 360° handle
- ▶ Wired control via ethernet & Wi-Fi
- ▶ Weight: 14 kg
- ▶ Suitable to use with DR and CR



APPLICATIONS


- Industrial** In-service Aviation & Aerospace, Power Plants, Petrochemical Plants, Composites Materials
- Aero / Space** Designed with BAM & Airbus to meet and exceed the requirements of In service Aviation & Aerospace applications.
- High precision** Spatial resolution improvement due to zoom magnification
- Portability** Due to μGemX-120 light weight and independency from the power sources, you can make extremely high quality images anywhere anytime !
- Real Time** Real time adjustment of the x-ray parameters when used with XRIS DR Systems.

ADVANTAGES

- Sharpness** The micro focal spot, the power and the rhythm of work of the μGemX-120 provide enhanced image quality:
 - ▶ Zoom magnification
 - ▶ No sharpness
 - ▶ Answer to DDA use on curved objects
- Lighter** Light weighted and all in one x-ray generator
Unique 360° handle to shoot in any direction
- Geometrical Magnification** μGemX-120 enables you to apply geometrical magnification on the field due to its μfocus tube (0,2mm), this will enlarge your capabilities on field with no compromise from the Class B quality
- Geometrical** Due to its very small focal spot you can **avoid geometrical distortion** when you make inspection on curved objects like pipes

GEOMETRICAL MAGNIFICATION

▶ Class B improvement with μ GemX-120 :



		Flat panel pixel size		
		200 μ m	140 μ m	96 μ m
T h i c k n e s s	Class B			
	... ; 1.5			
	1.5 ; 4			
	4 ; 8			
	8 ; 12			
	12 ; 40			
	40 ; 120			
	120 ; 200			
	200 ; ...			
Without zoom magnification				

- ▶ 200 μ m Pixel Size - Thickness : 120 mm \rightarrow 8 mm
- ▶ 140 μ m Pixel Size - Thickness : 40 mm \rightarrow 4 mm
- ▶ 96 μ m Pixel Size - Thickness : 8 mm \rightarrow 1.5 mm

OPTIONAL EXTRAS

- ▶ Tube
 - Window : aluminum (0,75 mm Aluminium equivalent)
 - Focal spot : 200 μ m
 - (Other tubes upon request)
- ▶ Power supply
 - 28-35 Vdc
 - Standard LiPo batteries (> 30 minutes of continuous X-ray at 120 kV - 1 mA)
 - Advanced LiPo batteries (**NEW : + 60% energy**)
 - Universal Vac power supply
- ▶ Control possibilities
 - Integrated keyboard on the μ GemX-120
 - Ethernet communication for computer control (**NEW**)
- ▶ Miscellaneous
 - μ GemX-120 is CE marked
 - Complies with international standards
 - Flashing lights and buzzers available
 - μ GemX-120 does not contain any greenhouse gases under high pressure

APPLICATION SHEETS

Detailed descriptions of applications carried out with our X-ray solutions are available on www.xris.eu

www.xris.eu